


Odyssey 3E

Polycarbonate External Sounder & Strobe Unit

The Odyssey 3E brings a new dimension to style and performance for residential sounders. Incorporating Texecom's patented safety engineer hold-off mode for easy installation and using the same microprocessor technology as the high end Odyssey Series, the reliable and cost-effective Odyssey 3E proves to be the shape of things to come.

Outstanding features:

- 109db Volume
- Polycarbonate Construction
- High Voltage Protection Circuitry
- Lid & Wall Tamper
- Patented Safety Engineer Hold-off Mode
- Twin Alternating LEDs
- Advanced Microprocessor Technology
- Strobe Tube Saver
- Selectable SAB/SCB Mode
- Low Current Mode
- EN 50131 Grade 3



Texecom
Designed to Perform



Patented Engineer Hold-off Mode

Installation and maintenance is made quick, simple and safe by a revolutionary patented safety engineer hold-off mode. On power-up the hold-off mode is automatically enabled, preventing the unit from sounding until the tamper circuit is secure. This enables "one trip up the ladder" installation. Hold-off mode can be re-invoked at any time from the control panel, ensuring easy maintenance and verification.



IP44 Sealed Electronics Module

The advanced electronics of the Odyssey 3E are protected by a robust inner cover and terminal block cover assembly. This provides protection from all the elements ensuring reliability in harsh conditions. Removal of the main PCB cover is unnecessary during installation. Access to the wiring connectors is made easy by simply unclipping the small terminal cover thereby guaranteeing a totally safe installation.



Dual Tamper Detection

Lid and wall tamper detection is provided as standard. Wall tamper is derived from a fixing screw location, removing the need to drill additional fixing holes and providing optimum reliability.

Specifications

Supply Voltage:	13.7V (nominal)		
Current Drain			
Quiescent (inc charging):	15mA		
Strobe:	100mA		
Sounder:	SAB	LC	SCB
	285mA	160mA	30mA
Battery:	NiMh Stack, 7.2Vbc, 320mAh		
Strobe:	1W, 1Hz Flash Rate		
Dimensions:	315mm x 306mm x 78mm		
Packed Weight:	1250g (450z) approx		

European Standards

Safety: Conforms to European Union (EU) Low Voltage Directive (LVD) 73/23/EEC (amended by 93/68/EEC).

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC).

Approved to BS EN 55022 Class B and BS EN 50130-4 : 1996.

PD 6662 & EN 50131-1 Grade 3 Environmental Class IV.

The CE mark indicates that this product complies with the European requirements for safety, health, environmental and customer protection.

Texcom products are protected by UK and International patents, trademarks and registered design rights.

UK Registered Design Number 2086725. © 2009 Texcom Limited.

Odyssey is a trademark of Texcom Limited. (LIT-0033)



Certificate Number: FM 35285

